



**Proofvision Outdoor range offers a great solution to displaying video outside come rain or shine.**

-  **Full HD LED Panels**
-  **Anti-reflective screen**
-  **Auto brightness adjustment**
-  **Toughened glass**
-  **IP 66 Rated with a slim and compact design**

Technical specifications	
Display size . . . . .	55"
Resolution . . . . .	1920*1080
TV format . . . . .	1080p
Aspect ratio . . . . .	16:9
Contrast Ratio . . . . .	5000:1
Brightness . . . . .	1500 cd/m2
Viewing angle . . . . .	178 degree /178 degree (H/V)
Max power consumption . . . . .	≤160W
Power input range . . . . .	AC 110 – 240V
TV systems . . . . .	PAL
Signal input . . . . .	Analog /DVB-T(freeview)
Audio System . . . . .	D/K,B/G,I,M
Multilanguage OSD . . . . .	YES
VGA . . . . .	1PC
AV . . . . .	1Group
YPbPr . . . . .	1Group
HDMI . . . . .	2PCS
RF . . . . .	1PC
RS232 . . . . .	1PC
IR OUT . . . . .	1PC
PC Audio . . . . .	1PC
USB . . . . .	1PC
Audio out . . . . .	1pc
Waterproof remote control . . . . .	1 pc
Batteries . . . . .	1 pc
User Manual . . . . .	1pc
VESA standard . . . . .	400mm*200mm
Screw . . . . .	4pcs
Operation temperature . . . . .	-20 to 60 degree
TV Dimension . . . . .	1272mm*755mm*76mm
Weight . . . . .	45kg
Frame material . . . . .	Aluminium